

MTR-18 Precision System Triangle

Clamping Angles (Pair)

Two provided angles can attach to the face of the triangle, providing large clamping surfaces to square cabinets during glue-up.

Indexing Pointer

Precision machined indexing pointer features an innovative zero-parallax viewport and dual holes accepting the included bench dogs, and t-bolt.

DoubleGroove™ Close Fit Bench Dogs (Pair)

These bench dogs feature a 19.98mm body providing a near zero clearance fit when inserted into a 20mm bench dog hole. Ideal for worktops made via precision CNC or The Parf Guide System.

Stowage Tin & Extra Hardware

Ergo Knob & T-Bolt

When you've found the perfect angle for your MTR-18, this knob locks the triangle body and indexing pointer together.

DoubleGroove™ Standard Fit Bench Dogs (Pair)

These bench dogs feature a 19.90mm body, ideal for use with the Festool® MFT/3 MultiFunction Table. Each dog includes an M8x1.25 threaded hole accepting standard clamping knobs such as TSO Products® SpeedKnobs™ or Festool® 488030 Clamping Element knobs.

Knurled Brass Knob

Cardinal angles of 0, 15, 22.5, 30, and 45 degrees can be quickly set with this precision machined knurled brass pin, which slides through the indexing pointer and into the holes on the triangle body.

Allen Drivers

SpeedKnobs™

High quality clamping knobs for DoubleGroove™ Bench Dogs.

Edge Locator Pins

Included short and long M6 index pins can be attached to one side of the triangle's face, to serve as a single-sided foot. Use the long pins to square your Festool® MFT/3 guide rail when raised.

Removeable Foot

Enables freestanding use or quick angle measurement off the edge of your table or workpiece. Includes ball-tip Allen wrench and stainless steel socket screws which can be conveniently stowed in tapped holes along the foot when not in use.

