



99	L (MAX.)	A MM. (MIN.) IN.	B (MAX.)	S (MAX.)	T (MAX.)	U		(K)	CB	CE
4"	114	13 1/2"	35	9.5	4.5	5.7	6.8	52	6	10
6"	160	19.2 3/4"	49	10.8	5.8	7.7	8.9	130	6	10
8"	206	24.05 15/16"	62	13.5	7	9.7	10.9	250	6	10
10"	257	29 1 1/8"	73	16	8	11.2	12.4	410	3	10
12"	310	34 1 3/8"	85	19	10	13.2	14.4	690	3	5
15"	386	43.12 1 11/16"	106	25	14.2	14.5	16.2	1.320	-	1
18"	462	53 2 1/8"	124	30	16	15.5	17.2	2.040	-	1

Sizes are shown in millimetres unless otherwise indicated.

MOD. 99

MOD. 99



THE IREGA GUARANTEE
 All IREGA wrenches are manufactured to the highest standards and are guaranteed against any default in workmanship and materials for the life of the tool. In the unlikely failure of one of our IREGA wrenches, please contact your usual supplier.



IREGA, S.A.
 Trianas 15
 01006 Vitoria (Spain)
 Tel.: +34 945 13 87 66
 Fax: +34 945 13 75 83
 E-mail: tools@irega.es
 www.irega.es



© JI & Asociados 609 42 92 68



Perfectly parallel jaw surfaces ensure perfect grip of nut.

Metric measuring scale on jaws for easy jaws presetting and sizing of nuts, bolts, pipes, etc. (also available in inches).

Non-protruding jaw shank. Great accessibility in tight spaces.

Thinner and longer jaws. Top functionality and torque.

Precision-ground jaw slides ensure smoother action and accurate adjustment of jaw & handle.

Double security. Threaded Pin and visible Stake for working under extreme conditions.



Model 99

A 15° adjustable wrench

This 15° adjustable wrench completes IREGA's line of products, providing the **widest range of adjustable wrenches on the market.**

Available in 7 Sizes (4" to 18"), phosphate Finish and left turning only.

Manufactured according to the most stringent International Standards and exceeding **UNE 16-532, ISO 6787, ASME B107.8M, BS ISO 6787** and **DIN 3117.**

CHROME VANADIUM steel. Great resistance, minimum wear, unbeatable durability.

Ergonomic handle design makes work easier and more efficient.

Every tool is individually inspected to Guarantee Total Customer Satisfaction.

Identification code. Full traceability.

